

## List of cable specifications

Model name	AWG	Wire standard outline	Insulation standard	Cable outer	Cable allowable bending radius	Remarks
P-7100	26	φ0.48	φ1.02	φ1.02	13.0 mm	Lead wire
		φ0.48	φ1.00	φ3.80	31.0 mm	1.5m cable
PA-20	26	φ0.58	φ1.00	φ3.20	26.0 mm	
PA-500	26	φ0.48	φ0.78	φ3.60	29.0 mm	
PA-75 *	22	φ0.76	φ1.65	φ5.30	43.0 mm	
PA-800	26	φ0.48	φ0.78	φ3.60	29.0 mm	
PA-83 *	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PA-838-D	22	φ0.78	φ1.50	φ4.00	32.0 mm	
PA-85 *	22	φ0.76	φ1.26	φ4.03	33.0 mm	
PA-86 *	22	φ0.76	φ1.36	φ4.90	40.0 mm	Signal line
		φ0.80	φ1.60			Shielded wire
PA-87 *	22	φ0.76	φ1.36	φ4.90	40.0 mm	Signal line
		φ0.80	φ1.60			Shielded wire
PA-92 * S cable	26	φ0.48	φ1.30	φ4.60	37.0 mm	
PA-930	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PA-930-A	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PA-97 * S cable	22	φ0.76	φ1.65	φ5.30	43.0 mm	
PS20	26	φ0.58	φ1.00	φ3.20	26.0 mm	
PS30	26	φ0.48	φ1.00	φ4.00	32.0 mm	
PS40	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PS6	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PS60	26	φ0.48	φ1.00	φ4.00	32.0 mm	
PS8	26	φ0.48	φ0.78	φ3.60	29.0 mm	
PS83	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PS85	22	φ0.76	φ1.26	φ4.03	33.0 mm	
PS86	26	φ0.48	φ1.05	φ4.80	39.0 mm	
PS87	26	φ0.48	φ1.05	φ4.80	39.0 mm	
PS91	26	φ0.48	φ1.00	φ3.80	31.0 mm	
PG-20	26	φ0.48	φ1.00	φ3.70	30.0 mm	
PG-30/35	26	φ0.48	φ0.90	φ3.80	31.0 mm	
PG-75	26	φ0.48	φ0.90	φ3.80	31.0 mm	
PZ-30	26	φ0.48	φ0.90	φ3.80	31.0 mm	
WL10	28	φ0.38	φ0.67	φ2.90	24.0 mm	

\* Cable allowable bending radius. Allowable bending radius is not the value guaranteed by the cable manufacturer, but the value recommended in the Electric Wire Handbook